

Docket #72354

PROCESS AND DEVICE FOR PRODUCING COLORED STREAMS OF FLUID FOR HOT WATER FITTINGS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a United States National Phase application of International Application PCT/DE2005/000579 and claims the benefit of priority under 35 U.S.C. § 119 of German Patent Application DE 10 2004 017 736.8 filed April 13, 2004, the entire contents of which are incorporated herein by reference.

5

FIELD OF THE INVENTION

[0002] The present invention pertains to a process for producing colored streams of fluid and a device for the application of the process.

BACKGROUND OF THE INVENTION

[0003] Giving a white or colored appearance to the streams of fluid escaping from water outlet fittings, fountains, artificial waterfalls and the like for achieving optical effects is known.

To this end, light sources are used, whose light waves are fed into the medium. The intended

5 light effects are achieved by the impacting of the light waves on the edge of the outflowing water jet and onto a medium, such as, for example, a wash basin. The light effect over the entire length of the water jet is produced by the reflection of the directed light waves within the water jet, as it is well known of fiberglass cables. Light, color and light effect are defined as visible color signals that are perceived by the normal-sighted eye in the fluid or at the site of the impact of the fluid.

10 **[0004]** Thus, a fluid nozzle, which is provided with an illumination source for achieving a white or colored water jet, is known from the Patent EP 0181 896 B2. The illumination source comprises a lighting means, which in 14 different embodiments is located either directly at the outlet opening of the fluid or at a site at a distance therefrom. So that as little illuminating power as possible is lost in the dispersion of the light up to the outlet opening of the fluid, means are

15 provided for low-loss guiding of the light. The lighting means are placed within the water outlet fitting, fountain or artificial waterfall either outside the supplied fluid or in the fluid itself. It is thus achieved by suitable means that the fluid does not come into contact with the lighting means and the electrically conductive parts. In order to achieve a change in the color of the water jet, a rotatable prism or an optical grid can be placed in front of the illumination source. By means of

20 the present invention, a water jet can be effectively lit up in bold colors.

[0005] Another white or colored, illuminating water jet for an ornamental fountain is known from the Patent US 6 393 192 B1. The water circulates constantly in the circuit from a basin via a system of pipelines to an outlet pipe placed higher, from where, as a free water jet, it again flows back into the basin. The motion of the water is produced by means of a pump. The light effect of the water is produced by means of a light source located outside of the water circuit. A fiberglass cable is led from this light source in a watertight manner into the system of pipelines up to the outlet pipe. It ends just before the outlet opening, where the light beam passes into the water.

[0006] Furthermore, an artificial waterfall, in which light from a light source is guided to the lower edge of a water outlet opening by means of a fiber optic cable, has become known from the Patent US 6 375 342 B1. In this case, the fiber optic cable is arranged such that the illuminating ends of the individual fibers are located in a certain association with one another under the water outlet.

[0007] Moreover, a light shower for use in showers has become known from the Utility Model DE 299 00 790 U1. The shower head is provided on the inside with a light source, which lights up the jets of the exiting water by means of a dispersing disk and the light is disseminated into the water jets.

[0008] With these prior-art solutions acknowledged above, an effective effect is achieved by means of the illuminating water jets which is perceived by the observer as beautiful, calming

and aesthetic.

[0009] Fittings, which are actuated by means of an actuating element or by means of a contact-free involvement of a person, make recognition of individually set water temperature ranges impossible, since the medium emerges only in case of detection by a person and thus a presetting is necessary. This requires a trying out of the operating temperature by using and holds the dangers of scalding by emerging hot water or, in the reverse case, of reducing a person's body temperature due to too cold medium.

[0010] When preparing a bath, there is often the problem that the manually set water temperature does not remain constant over the entire intake duration. The determination of the temperature is sensed at certain intervals one after another by the water admitted into the bathtub and by the water intake. An adjustment is then made, if necessary. In order to cut down on the hand contact needed for the determination of the water temperature, it is known to use water outlet fittings equipped with temperature indicators. If the inlet temperature shows a deviation from the set value, an adjustment is made manually.

[0011] Furthermore, a single-lever fitting, which is equipped with an actuating element for the automatic setting of a special mixing ratio of cold and hot water for the immediate preparation of water of a certain temperature, has become known from Unexamined Published Patent Application DE 102 19 171 A1. Such a fitting is particularly suitable for public facilities, where different users can wash their hands, without the water temperature having to be reset each time

by adjusting and testing. Actuating elements for regulating the water temperature can be angle of inclination pickups and/or acceleration pickups that are functionally connected to the mixing lever. The desired water temperature is set at the beginning. All the subsequent users will then have water of a comfortable temperature for hand washing. Thus, the water consumption is lowered, because an adjustment of the water temperature, in which a certain quantity of water runs off in a useless manner, is no longer necessary. Moreover, the risk of scalding the hands because of a mixing ratio being set too hot is avoided. If the fitting shall discharge water at a different temperature, this fitting is reset.

[0012] A water jet illuminator, which comprises a beam former that can be screwed at the output of a hot water fitting and thus extends the water outlet channel of the fitting, is already known from the publication DE 201 02 857 U1. Light-emitting diodes of various colors are arranged in the interior of the beam former. They are enclosed by a tubular light guide, which leads, in terms of flow technology according to the perlator, from outside by means of a curvature into the axis of the water jet. Two diodes, which are electrically connected to one another by means of the conductivity of the water, protrude into the through opening of this beam former, as soon as the hot water fitting was opened. A switching means consisting of electronic components, which is supplied with energy by means of a battery, is provided for this purpose. The water temperature is measured by means of a temperature sensor, and the measured result is fed to an electronic analyzer, which, depending on the measured water temperature, switches light-emitting diodes of a certain color or of a different combination of colors on or off. Thus, the present water temperature is signaled to the user of the water faucet after turning on by means of

the color of the water jet.

SUMMARY OF THE INVENTION

[0013] The object of the present invention is to create a process and a device for application of the process for a simple way to recognize the temperature of the water flowing out of a hot water outlet fitting fed with hot and cold water by means of a temperature-dependent change in the color of the water jet, on the basis of which, if necessary, a manual adjustment can be made for correction of the water temperature. The device is able to be placed in the hot water outlet opening, such that the freely visible part of the fitting does not have to be enlarged. Furthermore, the light beams coming from the light means shall be fed into the water jet in an as low-loss manner as possible.

[0014] This object is accomplished according to the present invention by the process according to claim 1 and the device according to claim 5. This is accomplished in that light-emitting diodes [sic, are? - Tr.Ed.] arranged directly in the area of the water outlet, and the water jet flowing out of the fitting is caused to have a colored appearance by means of the light-emitting diodes in a temperature-dependent manner at fixed temperature stages. A preferred temperature range is determined, [and] the temperatures lying above it and below it form two other ranges. Each of these ranges receives a certain color. In conjunction with the identification of red for hot water and blue for cold water, it is suggested to use red for the upper range and blue for the lower range. A third color is selected for the preferred middle temperature range, which may also be called the desired temperature range.

[0015] The process according to the present invention provides that the device switches

on with the increase in the pressure in the mixing chamber. This condition is reached with the

opening of the water inflow. The temperature of the water located in the mixing chamber is still

measured before the discharge from the mixing faucet. This actually present temperature is

5 assigned to the range in question, i.e., "too cold," "desired temperature range," or "too hot." In

addition, the lighting means of the color affecting the range is switched on and the user recognizes

by the color of the water jet whether or not a correction is necessary. If the water jet lights up in

a color that indicates a too cold or too hot temperature, a correction is made by the user by means

of an adjustment until the color of the water jet is identical to the desired range of the

10 temperature. This actual condition is indicated by the color in question, which is still achieved in

the mixing chamber before the escape of the water from the outlet fitting. After the closing of the

fitting, the device is switched off by means of recognizing the drop in pressure. The process is

operated with weak current.

[0016] The device consists of a pressure switch, by means of which it is switched on and

15 switched off in a pressure-dependent manner. A pressure sensor, which is arranged in the mixing

chamber of the fitting, is provided as pressure measuring point. This pressure switch is

functionally connected to the control block. With the buildup of the operating pressure in the

mixing chamber, the pressure switch switches on the control block. This control block receives

signals from the temperature sensor, which is likewise arranged in the mixing chamber, which it

20 recognizes as the temperature of the mixed water. The temperature actually present in the mixing

chamber is assigned in the control block to one of the three temperature ranges and lighting means

with the color assigned to the range is switched on. These lighting means are diodes, which are arranged in each of the three colors in a sufficient number on a multichip. This multichip is arranged together with the perlator in the outlet opening of the fitting. In this case, the multichip and the perlator form a protection against external effects for the diodes. To guarantee a
5 sufficient permeability of the water, the multichip is provided with openings. The color radiation of the water flowing past the light-emitting diodes at the output of the fitting is continued in the water jet and lights this up in the [sic, color? - Tr.Ed.] in question. For regulating [sic, "Reglung" is an obvious typo for "Regelung" - Tr.Ed.] the water temperature, the user actuates the lever, so that the feed stream of the portions of cold water and hot water are [sic, is - Tr.Ed.] changed. A
10 transformer is provided for supplying the control block and the light-emitting diodes with weak current.

[0017] The following advantages are connected with the application of the present invention:

1. No light losses occur by means of introducing the light at the water outlet. A high dispersion
15 of light is achieved.
2. The entire device has a small space requirement, such that it can be placed in a hot water fitting of a standard size.
3. The transformer is arranged under the wash basin, such that it is not visible with its supply line.
- 20 4. Emotional comfort effect due to an illumination in the luxus range (AHA effect).
5. Energy-saving effect due to saving of hot water.

6. Prevention of scaldings due to temperatures above 38°C by children and disabled people/senior citizens/persons with diabetes mellitus.
7. Integration in the field of gerontology/people with skin disability for recreation and meditation.
- 5 8. *Legionella* water hygiene management (prevention of deaths due to formation of *Legionella* in standing water) >55°C for compliance with DVGW W 551 and W 552.
9. Color therapy with green (against stress and hectic state).
10. Prevention of cooling off of body parts exposed to cold water, which are felt to be unpleasant.
11. Measurement of the water pressure and of the water temperature right at the start of the water
- 10 channel in the mixing chamber of the fitting, such that a fast startup and response of the device is possible.

[0018] An exemplary embodiment of the present invention is shown in the drawing. The various features of novelty which characterize the invention are pointed out with particularity in the claims annexed to and forming a part of this disclosure. For a better understanding of the invention,

15 its operating advantages and specific objects attained by its uses, reference is made to the accompanying drawings and descriptive matter in which a preferred embodiment of the invention is illustrated.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] In the drawings:

[0020] The only Figure is a schematic block view with diagram showing a control loop and a controlled system view for a single-lever water outlet fitting.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0021] Referring to the drawings in particular, the drawing shows the block diagram with a control loop and a controlled system view for a single-lever water outlet fitting. This is referred to simply as fitting below.

[0022] In the drawing, the fitting is shown in a simplified manner and schematically in a sectional view. In principle, the fitting comprises the basic body 1 and the outlet pipe 2. The internal diameter 3 of the output pipe 2 is reproduced by means of a circle. The lever 4 for the manual release of the water feed, which is shown in broken lines, is located on the basic body 1. The outlet opening 5 for the water is provided with a perlator (outlet end device - aerator, flow distributor screen) 6. The mixing chamber 7, to which the outlet pipe 2 is connected, is located in the interior of the basic body 1. The two pipelines 8, 9 for the cold water (KW) and the hot water (WW) lead to the mixing chamber 7. The fitting is equipped with a pressure switch 10, which is functionally connected via a pipeline 11 to a pressure sensor 12 arranged in the mixing chamber 7. Furthermore, the fitting includes a control block 13 and a transformer 14. The control block 13 is supplied with weak current by means of the transformer 14. From the control block 13, a pipeline 15 leads to a temperature sensor 16 arranged in the mixing chamber 7. A multichip (printed circuit board) 18, equipped with light-emitting diodes (LED), 17 is arranged in front of the outlet opening in the interior of the outlet pipe 2. Red light-emitting diodes 17R, blue light-emitting diodes 17B and green light-emitting diodes

17Gr are used and installed on the printed circuit board 18. These light sources 17 are arranged in the necessary number and the selected colors on the multichip 18 with blue light-emitting diodes 17B, green light-emitting diodes 17Gr and red light-emitting diodes 17R and are switched via the low-voltage line 19, such that a color effect, intended in their appearance, develops in the fluid jet or water stream 20. The number of light-emitting diodes 17 of each color depends on the light intensity of the diodes 17 used and on the overall light intensity that shall be achieved. Instead of blue, green and red light-emitting diodes 17, the RGB-LED, which are available as a new development, may also be used, in which the three colors red, green and blue are available in a component. The multichip 18 equipped with the light-emitting diodes or diode component 17 is integrated into the perlator or outlet 6 and as a set of components is thus protected against external effects. It is also possible to install the color diodes 17 directly in the perlator 6 without the printed circuit board.

[0023] For the appearance of the water jet or water stream flowing out of the water outlet fitting, the following three colors are set in a temperature-dependent manner:

- for cold water of the range up to circa 18°C - blue water color
- for hot water of the range 19°C-38°C - green water color
- for hot water of the range over 38°C - red water color.

These temperature ranges and the color selection are not absolute, they may also be set differently.

[0024] The lever 4 is actuated for releasing a water jet water stream 20 from the fitting. Depending on the position of the lever 4, either only cold water, only hot water or proportionately cold and hot water is let into the mixing chamber 7. By means of the pressure sensor 12, the pressure

buildup in the mixing chamber 7 is detected. Due to this pressure buildup, the control block 13 is put into operation via the pressure switch 10. In this case, a contact releases the circuit. The control block 13 receives signals from the temperature sensor 16, which it recognizes as the actually present temperature. By means of the control block 13, the light-emitting diodes 17B, 17Gr and 17R of the color determined for the respective temperature range are now lit up on the printed circuit board 18. The desired color is introduced into the fluid. The user of the fitting can recognize the temperature of the water from the colored appearance of the water jet 20 and thus, if necessary, can make a correction by means of actuating the lever 4 at a time before the water is in contact with the hand.

10 **[0025]** The closing of the water feed is detected as a drop in pressure by the pressure sensor 12 and the device is switched off.

[0026] Effective color displays may likewise take place without/with temperature change with the three basic colors red, green and blue, including all mixed color shades.

15 **[0027]** It is also possible to provide light-emitting diodes 17 of the colors red, yellow and blue and to mix these primary colors additively, so that the colors determined for the respective temperature ranges are formed. To this end, the control block 13 is designed correspondingly.

[0028] If the temperature-dependent color change in the water jet is temporarily not needed, it is also possible to produce a color play (display) with the light-emitting diodes 17 in a temperature-independent manner. To this end, a switch can be provided for changing the type of operation.

[0029] A fitting thus equipped can be used on wash basins, sinks, bathtubs, showers and other sites for the removal of water of a preferred temperature range.

[0030] While specific embodiments of the invention have been described in detail to illustrate the application of the principles of the invention, it will be understood that the invention may be

5 embodied otherwise without departing from such principles.